


it's NEW...it's NEWS! From the Home of the ATOM







These popular, pre	cision engineered units are still available
ECE 2-A Re	ceiver\$12.50
ECE 4-A Re	ceiver 12.95
ECE Univer	sal Installation Kit 1,98
ECE T-11 Te	ansmitter

The Cold Facts About the Hottest Three Channel % Equipment Available to the Contest Flyer or the Sport Pilot

ECE's new hand-held multi-channel T-15 Precision Transmitter for full control of rudder, elevators and throttle. Push the button and outstunt and outfly them all. Easier to operate.

ECE's new R-6 Receiver can "take" it. A giant performer in smallest size and lightest weight available, the R-6 operates on lowest plate and filament voltages and gives you longest battery life.

ECE's new M-3 Modulator guarantees you the last word in stability. Once tuned, the oscillator maintains its frequency.

T-15 TRANSMITTER SPECIFICATIONS

- Single channel CW operation or tone modulated for multi-channel operation (when used with the M-3 Modulator)
- Crystal controlled to transmit on FCC license free band at 27.25 MCS
- Crystal damage proof when operated without antenna
- 60 inch chrome plated telescoping antenna
- Weight: approximately 4 pounds
- Rugged, precision construction
- Single screw tuning from the front
- Pre-tested and tuned before shipment
- Power input: 3 watts maximum
- Power requirements:
 Filament: CW operation-1½ volts 200 MA. Tone operation-1½ volts 350MA
 Plate: CW operation-135 volts 20MA (key down). Tone operation-135 volts 10MA continuous

ONLY \$29.95

R-6 RECEIVER SPECIFICATIONS

- 3 Channel tone receiver using tuned reeds for channel discrimination
- Rugged, compact construction
- Weight-Approximately 8 ozs. (with batteries about 13 ozs.)
- Pre-tested and tuned before shipment
- · High sensitivity for reliable range
- Easy installation through one plug connection
- Tone frequencies between 225 and 500 cps
- Power requirements: Filament: 1½ volts at 270MA
 Plate: 45 volts at 2.5MA idle, 6MA when signal is on
- Maximum battery life: Recommended batteries: 2 Burgess U-15 or equivalent and one D size 1½ volt flashlight battery

ONLY \$79.95

Convert Your Present T-15 to Multi-Channel—It's Easy!

If you have the single-channel T-15 Transmitter now, you can convert it quickly and simply to three-channel precision control in a matter of minutes. No soldering necessary. The ECE M-3 Modulator can be installed in your T-15 with just a screwdriver.

By this progressive method of changeover from one-channel to multi-channel R/C, ECE makes it simple and inexpensive for you to move ahead in flying performance.

M-3 MODULATOR SPECIFICATIONS

- Three channels of tone for positive multi-control when used with the T-15 Transmitter
- Oscillator of modern design...unusual stability...once tuned, oscillator maintains frequency.
- Tuning controls accessible from exterior of cabinet
- Frequency range from 220 to 600 cycles per second
- 85% minimum modulation to prevent receiver blocking...exceptionally good wave form.

ONLY \$29.95

All ECE equipment is available at your local hobby supply dealer. If your dealer is out of stock, write us for further information.





305 Dallas Street, N. E. Albuquerque, New Mexico